

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-258888

(43)Date of publication of application : 08.10.1996

(51)Int.Cl.

B65D 85/86  
B32B 27/00  
B32B 27/28  
H01L 21/68

(21)Application number : 07-063644

(71)Applicant : SUMITOMO BAKELITE CO LTD

(22)Date of filing : 23.03.1995

(72)Inventor : MIYAMOTO TOMOHARU

## (54) COVER TAPE FOR EMBOSSING CARRIER TAPE FOR SURFACE COATING

(57)Abstract:

**PURPOSE:** To prevent a cover tape from being cut on peeling off the tape, by laminating a biaxially oriented film as an external layer, a specified ethylene-cr- olefin copolymer as an intermediate layer, and a specified coating film as an adhesive layer.

**CONSTITUTION:** The external layer 2 is either biaxially oriented polyester film or polypropylene film. The intermediate layer 4 is an ethylene- $\alpha$ -olefin copolymer polymerized with a metallocene catalyst, which is 100kg/cm or more in tear strength (JISK7128), 100kg-cm/cm<sup>2</sup> or higher in tensile impact strength (ASTM D1822), 15% or lower in opaqueness (JISK7105). The adhesive layer 5 has a characteristic heat-sealing the opposite plastic carrier tape by either polyurethane or acrylic resin-heat seal lacquer type thermoplastic adhesive or the combined material thereof. An electrically conductive fine powdered material of either tin oxide or zinc oxide is homogeneously dispersed in the adhesive.

